

SAFETY DATA SHEET

In accordance with UN GHS latest edition

Product: V-SCREEN+ TROPICAL PUNCH VSC51

Version: 1

Section 1. Identification of the substance or the mixture and of the supplier

1.1 Product Identifier

Product identifier: V-SCREEN+ TROPICAL PUNCH VSC51(Contains:Linalyl acetate, [1.alpha.(E),2.beta.]-1-(2,6,6-Trimethyl-3-cyclohexen-1-yl)-2-buten-1-one)

Other identifiers: None

1.2 Relevant identified uses of the substance of mixture and uses advised against

Product uses: Urinal Screen,For Professional use only.

Uses advised against: Use only for intended applications

1.3 Details of the supplier of the safety data sheet

Company name: Vectair Systems Ltd.

Company address: Unit 3, Trident Centre, Armstrong Road, Basingstoke, Hampshire, RG24 8NU, UK

Contact: Vectair Systems Ltd.

E-Mail address: prod-dev@vectairsystems.com

Company phone: +44 (0) 1256 319500 (Office Hours 09:00 to 17:00)

Responsible Person: Hygiene Systems Australia Pty Ltd.

Address: Unit 1,
2 Logistics Street,
Yatala,
QLD 4207,
Australia

Phone: +61 7 3801 8500

1.4 Emergency telephone number

Emergency phone: Queensland - Poisons Information Centre (24hrs) - 13 11 26
NZ - National Poisons Centre 24 hrs - 0800 764 766

Section 2. Hazards identification

2.1 Classification of the substance or mixture

Class and category of danger: Skin Corrosion / Irritation Category 3
Eye Damage / Irritation Category 2
Sensitization - Skin Category 1
Hazardous to the Aquatic Environment - Acute Hazard Category 2
Hazardous to the Aquatic Environment - Long-term Hazard Category 3
H316, Causes mild skin irritation.
H317, May cause an allergic skin reaction.
H319, Causes serious eye irritation.
H401, Toxic to aquatic life.
H412, Harmful to aquatic life with long lasting effects.

SAFETY DATA SHEET

In accordance with UN GHS latest edition

Product: V-SCREEN+ TROPICAL PUNCH VSC51

Version: 1

2.2 Label elements

Signal word: Warning.

Hazard statements: H316, Causes mild skin irritation.
H317, May cause an allergic skin reaction.
H319, Causes serious eye irritation.
H401, Toxic to aquatic life.
H412, Harmful to aquatic life with long lasting effects.

Precautionary statements: P280, Wear protective gloves/eye protection/face protection.
P302/352, IF ON SKIN: Wash with plenty of soap and water.
P305/351/338, IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P333/313, If skin irritation or rash occurs: Get medical advice/attention.
P337/313, If eye irritation persists: Get medical advice/attention.
P501, Dispose of contents/container to approved disposal site, in accordance with local regulations.

Pictograms:



2.3 Other hazards

Other hazards: Hydrocarbon Concentration %: 0.0000%

Section 3. Composition / information on ingredients

3.2 Mixtures

Contains:

Name	CAS	%	GHS Classification
Linalyl acetate	115-95-7	1-<5%	Flam. Liq. 4-Skin Irrit. 2-Eye Irrit. 2B-Skin Sens. 1B-Aquatic Acute 3;H227-H315-H317-H320-H402
Tricyclodecanyl acetate	5413-60-5	1-<5%	Acute Tox. 5-Skin Irrit. 3-Aquatic Acute 2-Aquatic Chronic 1;H303-H316-H401-H410
Benzenesulfonic acid, C10-13-alkyl derivs., sodium salts	68411-30-3	0.1-<1%	Acute Tox. 4-Skin Irrit. 2-Eye Dam. 1-Aquatic Acute 3-Aquatic Chronic 3;H302-H315-H318-H412
alpha-Hexylcinnamaldehyde	101-86-0, 165184-98-5	0.1-<1%	Acute Tox. 5-Skin Irrit. 3-Skin Sens. 1B-Aquatic Acute 1-Aquatic Chronic 2;H303-H316-H317-H400-H411
Linalool	78-70-6	0.1-<1%	Flam. Liq. 4-Acute Tox. 5-Skin Irrit. 2-Eye Irrit. 2A-Skin Sens. 1B-Aquatic Acute 3;H227-H303-H315-H317-H319-H402
Citral	5392-40-5	0.1-<1%	Skin Irrit. 2-Eye Irrit. 2A-Skin Sens. 1-Aquatic Acute 2;H315-H317-H319-H401
Cocamide MEA	68140-00-1	0.1-<1%	Met. Corr. 1-Skin Irrit. 2-Aquatic Chronic 2;H290-H315-H411

SAFETY DATA SHEET

In accordance with UN GHS latest edition

Product: V-SCREEN+ TROPICAL PUNCH VSC51

Version: 1

Ethyl methylphenylglycidate	77-83-8	0.1-<1%	Skin Sens. 1B-Aquatic Acute 2-Aquatic Chronic 2; H317-H411
beta-Pinene	127-91-3	0.1-<1%	Flam. Liq. 3-Skin Irrit. 2-Skin Sens. 1B-Asp. Tox 1-Aquatic Acute 1-Aquatic Chronic 1;H226-H304-H315-H317-H410
Allyl heptanoate	142-19-8	0.1-<1%	Flam. Liq. 4-Acute Tox. 3-Acute Tox. 3-Aquatic Acute 1-Aquatic Chronic 2;H227-H301-H311-H400-H411
dl-Citronellol	106-22-9, 7540-51-4	0.1-<1%	Acute Tox. 5-Acute Tox. 5-Skin Irrit. 2-Eye Irrit. 2A-Skin Sens. 1B-Aquatic Acute 2;H303-H313-H315-H317-H319-H401
1,3,4,6,7,8-Hexahydro-4,6,6,7,8,8-hexamethylcyclopenta-gamma-2-benzopyran	1222-05-5	0.1-<1%	Skin Irrit. 3-Aquatic Acute 1-Aquatic Chronic 1;H316-H410
Allyl cyclohexanepropionate	2705-87-5	0.1-<1%	Acute Tox. 4-Acute Tox. 4-Skin Sens. 1-Aquatic Acute 1-Aquatic Chronic 2;H302-H312-H317-H400-H411
d-Limonene	5989-27-5, 138-86-3, 5989-54-8	0.1-<1%	Flam. Liq. 3-Skin Irrit. 2-Skin Sens. 1B-Asp. Tox 1-Aquatic Acute 1-Aquatic Chronic 3;H226-H304-H315-H317-H400-H412
Octanal	124-13-0	0.1-<1%	Flam. Liq. 3-Skin Irrit. 2-Eye Irrit. 2A-Aquatic Acute 2-Aquatic Chronic 3;H226-H315-H319-H401-H412
Dihydromyrcenol	18479-58-8	0.1-<1%	Flam. Liq. 4-Acute Tox. 5-Skin Irrit. 2-Eye Irrit. 2A-STOT SE 3-Aquatic Acute 3;H227-H303-H315-H319-H336-H402
Allyl hexanoate	123-68-2	0.1-<1%	Flam. Liq. 4-Acute Tox. 3-Acute Tox. 3-Aquatic Acute 1-Aquatic Chronic 2;H227-H301-H311-H400-H411
2-Methoxy-4-methylphenol	93-51-6	0.1-<1%	Acute Tox. 4-Skin Irrit. 2-Eye Irrit. 2A-Skin Sens. 1B; H302-H315-H317-H319
[1.alpha.(E),2.beta.]-1-(2,6,6-Trimethyl-3-cyclohexen-1-yl)-2-buten-1-one	71048-82-3	0.1-<1%	Acute Tox. 4-Skin Irrit. 2-Skin Sens. 1A-Aquatic Acute 1-Aquatic Chronic 1;H302-H315-H317-H410
Dimethylcyclohex-3-ene-1-carbaldehyde	27939-60-2, 68039-49-6, 68039-48-5	0.1-<1%	Flam. Liq. 4-Acute Tox. 5-Skin Irrit. 2-Eye Irrit. 2A-Skin Sens. 1B-Aquatic Acute 2-Aquatic Chronic 2;H227-H303-H315-H317-H319-H411
Citronellal	106-23-0	0.1-<1%	Flam. Liq. 4-Acute Tox. 5-Acute Tox. 5-Skin Irrit. 2-Eye Irrit. 2A-Skin Sens. 1B-Aquatic Acute 2;H227-H303-H313-H315-H317-H319-H401

Substances with workplace exposure limits, not listed above:

Not Applicable

Section 4. First-aid measures

4.1 Description of first aid measures

Inhalation: Remove from exposure site to fresh air, keep at rest, and obtain medical attention.

Eye exposure: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Skin exposure: IF ON SKIN: Wash with plenty of soap and water.

Ingestion: Rinse mouth with water and obtain medical attention.

4.2 Most important symptoms and effects, both acute and delayed

Causes mild skin irritation.

May cause an allergic skin reaction.

Causes serious eye irritation.

SAFETY DATA SHEET

In accordance with UN GHS latest edition

Product: V-SCREEN+ TROPICAL PUNCH VSC51

Version: 1

4.3 Indication of any immediate medical attention and special treatment needed

None expected, see Section 4.1 for further information.

Section 5: Firefighting measures

5.1 Extinguishing media

Suitable media: Carbon dioxide, Dry chemical, Foam.

5.2 Special hazards arising from the substance or mixture

In case of fire, may be liberated: Carbon monoxide, Unidentified organic compounds.

5.3 Advice for fire fighters:

In case of insufficient ventilation, wear suitable respiratory equipment.

Section 6. Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures:

Avoid inhalation. Avoid contact with skin and eyes. See protective measures under Section 7 and 8.

6.2 Environmental precautions:

Keep away from drains, surface and ground water, and soil.

6.3 Methods and material for containment and cleaning up:

Remove ignition sources. Provide adequate ventilation. Avoid excessive inhalation of vapours. Contain spillage immediately by use of sand or inert powder. Dispose of according to local regulations.

6.4 Reference to other sections:

Also refer to sections 8 and 13.

Section 7. Handling and storage

7.1 Precautions for safe handling:

Keep away from heat, sparks, open flames and hot surfaces. - No smoking. Use personal protective equipment as required. Use in accordance with good manufacturing and industrial hygiene practices. Use in areas with adequate ventilation. Do not eat, drink or smoke when using this product.

7.2 Conditions for safe storage, including any incompatibilities:

Store in a well-ventilated place. Keep container tightly closed. Keep cool. Ground/bond container and receiving equipment. Use explosion-proof electrical, ventilating and lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

7.3 Specific end use(s):

Urinal Screen, For Professional use only.: Use in accordance with good manufacturing and industrial hygiene practices.

Section 8. Exposure controls/personal protection

8.1 Control parameters

Workplace exposure limits: Not Applicable

SAFETY DATA SHEET

In accordance with UN GHS latest edition

Product: V-SCREEN+ TROPICAL PUNCH VSC51

Version: 1

8.2 Exposure Controls

Eye / Skin Protection

Wear protective gloves/eye protection/face protection

Respiratory Protection

Under normal conditions of use and where adequate ventilation is available to prevent build up of excessive vapour, this material should not require special engineering controls. However, in conditions of high or prolonged use, or high temperature or other conditions which increase exposure, the following engineering controls can be used to minimise exposure to personnel: a) Increase ventilation of the area with local exhaust ventilation. b) Personnel can use an approved, appropriately fitted respirator with organic vapour cartridge or canisters and particulate filters. c) Use closed systems for transferring and processing this material.

Also refer to Sections 2 and 7.

Section 9. Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance:	blue Solid
Odour:	Fruity
Odour threshold:	Not determined
pH:	Not determined
Melting point / freezing point:	Not determined
Initial boiling point / range:	> 100 °C
Flash point:	100 °C
Evaporation rate:	Not determined
Flammability (solid, gas):	Not determined
Upper/lower flammability or explosive limits:	Product does not present an explosion hazard
Vapour pressure:	Not determined
Vapour density:	Not determined
Relative density:	Not determined
Solubility(ies):	Not determined
Partition coefficient: n-octanol/water:	Not determined
Auto-ignition temperature:	> 200 °C
Decomposition temperature:	Not determined
Viscosity:	Not determined
Explosive properties:	Not expected
Oxidising properties:	Not expected

9.2 Other information:

Volatile Organic Compound:	24.9000%
(CH) VOC % Switzerland:	24.900%

SAFETY DATA SHEET

In accordance with UN GHS latest edition

Product: V-SCREEN+ TROPICAL PUNCH VSC51

Version: 1

Section 10. Stability and reactivity

10.1 Reactivity:

Presents no significant reactivity hazard, by itself or in contact with water.

10.2 Chemical stability:

Good stability under normal storage conditions.

10.3 Possibility of hazardous reactions:

Not expected under normal conditions of use.

10.4 Conditions to avoid:

Avoid extreme heat.

10.5 Incompatible materials:

Avoid contact with strong acids, alkalis or oxidising agents.

10.6 Hazardous decomposition products:

Not expected.

Section 11. Toxicological information

11.1 Information on toxicological effects

This mixture has not been tested as a whole for health effects. The health effects have been calculated using the methods outlined in UN GHS.

Acute Toxicity: Based on available data the classification criteria are not met.

Acute Toxicity Oral >5000

Acute Toxicity Dermal >5000

Acute Toxicity Inhalation Not Available

Skin corrosion/irritation: Skin Corrosion / Irritation Category 3

Serious eye damage/irritation: Eye Damage / Irritation Category 2

Respiratory or skin sensitisation: Sensitization - Skin Category 1

Germ cell mutagenicity: Based on available data the classification criteria are not met.

Carcinogenicity: Based on available data the classification criteria are not met.

Reproductive toxicity: Based on available data the classification criteria are not met.

STOT-single exposure: Based on available data the classification criteria are not met.

STOT-repeated exposure: Based on available data the classification criteria are not met.

Aspiration hazard: Based on available data the classification criteria are not met.

Information about hazardous ingredients in the mixture

Ingredient	CAS	LD50/ATE Oral	LD50/ATE Dermal	LC50/ATE Inhalation	LC50 Route
Allyl heptanoate	142-19-8	218	810	Not available	Not available
Allyl hexanoate	123-68-2	218	300	Not available	Not available
Tricyclodecenyyl acetate	5413-60-5	2750	Not available	Not available	Not available

SAFETY DATA SHEET

In accordance with UN GHS latest edition

Product: V-SCREEN+ TROPICAL PUNCH VSC51

Version: 1

Refer to Sections 2 and 3 for additional information.

Section 12. Ecological information

12.1 Toxicity:

Harmful to aquatic life with long lasting effects.

12.2 Persistence and degradability: Not available

12.3 Bioaccumulative potential: Not available

12.4 Mobility in soil: Not available

12.5 Other adverse effects: Not available

Section 13. Disposal considerations

13.1 Waste treatment methods:

Dispose of in accordance with local regulations. Avoid disposing into drainage systems and into the environment. Empty containers should be taken to an approved waste handling site for recycling or disposal.

Section 14. Transport information

	14.1 UN number:	14.2 UN Proper Shipping Name:	14.3 Transport hazard class (es):	Sub Risk:	14.4 Packing Group:
UN Model Regulations	Not classified	-	-	-	-
IMDG	Not classified	-	-	-	-
ADR,RID,ADN	Not classified	-	-	-	-
ICAO TI	Not classified	-	-	-	-

14.5 Environmental hazards: Not environmentally hazardous for transport

14.6 Special precautions for user: None additional

14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code:

Not classified

Section 15. Regulatory information

SDS Reference No.: SD-000376S

SAFETY DATA SHEET

In accordance with UN GHS latest edition

Product: V-SCREEN+ TROPICAL PUNCH VSC51

Version: 1

Section 16. Other information

Concentration % Limits: SCI 3=12.92% EDI 2A=77.52% SS 1=33.33% EH A2=46.73% EH A3=4.65% EH C3=10.87%

Total Fractional Values: SCI 3=7.74 EDI 2A=1.29 SS 1=3.00 EH A2=2.14 EH A3=21.52 EH C3=9.20

Key to revisions:

Not applicable

Key to abbreviations:

Abbreviation	Meaning
Acute Tox. 3	Acute Toxicity - Oral Category 3
Acute Tox. 3	Acute Toxicity - Dermal Category 3
Acute Tox. 4	Acute Toxicity - Oral Category 4
Acute Tox. 4	Acute Toxicity - Dermal Category 4
Acute Tox. 5	Acute Toxicity - Oral Category 5
Acute Tox. 5	Acute Toxicity - Dermal Category 5
Aquatic Acute 1	Hazardous to the Aquatic Environment - Acute Hazard Category 1
Aquatic Acute 2	Hazardous to the Aquatic Environment - Acute Hazard Category 2
Aquatic Acute 3	Hazardous to the Aquatic Environment - Acute Hazard Category 3
Aquatic Chronic 1	Hazardous to the Aquatic Environment - Long-term Hazard Category 1
Aquatic Chronic 2	Hazardous to the Aquatic Environment - Long-term Hazard Category 2
Aquatic Chronic 3	Hazardous to the Aquatic Environment - Long-term Hazard Category 3
Asp. Tox 1	Aspiration Hazard Category 1
Eye Dam. 1	Eye Damage / Irritation Category 1
Eye Irrit. 2A	Eye Damage / Irritation Category 2A
Eye Irrit. 2B	Eye Damage / Irritation Category 2B
Flam. Liq. 3	Flammable Liquid, Hazard Category 3
Flam. Liq. 4	Flammable Liquid, Hazard Category 4
H226	Flammable liquid and vapour.
H227	Combustible liquid.
H290	May be corrosive to metals.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H303	May be harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H311	Toxic in contact with skin.
H312	Harmful in contact with skin.
H313	May be harmful in contact with skin.
H315	Causes skin irritation.
H316	Causes mild skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.

SAFETY DATA SHEET

In accordance with UN GHS latest edition

Product: V-SCREEN+ TROPICAL PUNCH VSC51

Version: 1

H319	Causes serious eye irritation.
H320	Causes eye irritation.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H401	Toxic to aquatic life.
H402	Harmful to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
Met. Corr. 1	Corrosive to Metals Category 1
P210	Keep away from heat, sparks, open flames and hot surfaces. - No smoking.
P233	Keep container tightly closed.
P234	Keep only in original container.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical, ventilating and lighting equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P261	Avoid breathing vapour or dust.
P264	Wash hands and other contacted skin thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P271	Use only outdoors or in a well-ventilated area.
P272	Contaminated work clothing should not be allowed out of the workplace.
P273	Avoid release to the environment.
P280	Wear protective gloves/eye protection/face protection.
P301/310	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
P301/312	IF SWALLOWED: call a POISON CENTER or doctor/physician if you feel unwell.
P302/352	IF ON SKIN: Wash with plenty of soap and water.
P303/361/353	IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower.
P304/340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P305/351/338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER or doctor/physician.
P312	Call a POISON CENTRE or doctor/physician if you feel unwell.
P330	Rinse mouth.
P331	Do not induce vomiting.
P332/313	If skin irritation occurs: Get medical advice/attention.
P333/313	If skin irritation or rash occurs: Get medical advice/attention.
P337/313	If eye irritation persists: Get medical advice/attention.
P361	Remove/Take off immediately all contaminated clothing.
P362	Take off contaminated clothing and wash before reuse.
P363	Wash contaminated clothing before reuse.
P370/378	In case of fire: Use carbon dioxide, dry chemical, foam for extinction.

SAFETY DATA SHEET

In accordance with UN GHS latest edition

Product: V-SCREEN+ TROPICAL PUNCH VSC51

Version: 1

P390	Absorb spillage to prevent material damage.
P391	Collect spillage.
P403/233/235	Store in a well-ventilated place. Keep container tightly closed. Keep cool.
P403/235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P406	Store in corrosive resistant container with a resistant inner liner.
P501	Dispose of contents/container to approved disposal site, in accordance with local regulations.
STOT SE 3	Specific Target Organ Toxicity (Single Exposure) Category 3
Skin Irrit. 2	Skin Corrosion / Irritation Category 2
Skin Irrit. 3	Skin Corrosion / Irritation Category 3
Skin Sens. 1	Sensitization - Skin Category 1
Skin Sens. 1A	Sensitization - Skin Category 1A
Skin Sens. 1B	Sensitization - Skin Category 1B

The information in this safety data sheet is to the best of our knowledge true and accurate but all data, instructions, recommendations and/or suggestions are made without guarantee.